

SPLICE ENCLOSURE SCD/LCQ/ST T-KNN00155

This splice enclosure is designed as a simple distribution box for indoor installation. The enclosure can be used for distribution of pre-connected cable or blown cable. It could be utilised in small building facility or as floor box. Ideal for FTTH networks.

Features

- Flat base with mounting holes
- Knock outs on back allowing for through the wall connection
- Can splice or patch
- Splice tray & cable management
- Two positions for adaptor plate
- Enables loop through cable connectivity

Included in each enclosure

Item	Qty	Size
Adaptor Plates	1	6 Way SC Duplex / LC Quad
	1	12 Way ST Simplex
Splice tray	1	12 fibres
Splice holder	1	12 fibres
Glands (OD)	PG 7	1 2.5 to 6.5 mm
	PG 16	1 8.0 to 16 mm
Cable ties	6	2.5 x100 mm
Cable holders	3	
Screws + anchors	2	6 mm
Screws for cable tray	2	
Double sided tape	1	60 x 12 mm
Graded rubber bushing (OD)	2	3.0 to 10mm



Rear panel showing the many mounting options available

Technical Specifications

Cable entry	Rear / 4 Sides	
Material	ABS	
Flame Retardant	V2 dle UL94	
Impact protection	IK6 to EN50102	
Colour	White RAL9003	
Dimensions	Height	205 mm
	Width	157 mm
	Length	60 mm
Weight	0.35 kg	
IP rating	IP 20	

